

## **WSS -3 0 3**

### **Product technical specification**

WSS -303 is for an aqueous, solvent-based , light-curable coatings and ink systems, can greatly enhance surface slip and substrate wetting properties, excellent compatibility .

- Significantly improved slip
- Fluidity, anti-blocking
- High efficiency , high compatibility (minimize the risk of fogging)
- Good recoatability , improved scratch resistance
- Effects of the minimal interlayer adhesion , to provide a smooth feel of leather topcoats

#### **Recommended Applications**

- Wood and furniture coatings

Recommended amount

In the form of supply to the total formula: 0.05-0.3 %

- Car paint

Recommended amount

In the form of supply to the total formula: 0.03-0.2%

- Leather top coat based on polyurethane, acrylic resin and nitro system

Recommended amount

Based on the supply form to the total formula: 0.1-1.0%

#### **Technical data**

Appearance: transparent liquid

Active matter content : 100%

Viscosity, 25 degree : about 300 in mPas

#### **Process Description**

Pre-diluted or directly added to the paint in the form of supply

Pre-dilution with the recommended solvent will facilitate addition and mixing

#### **chemical composition**

Organosiloxane copolymer

#### **package**

- 25KG , plastic bucket
- 200 kg , iron drum

#### **Storage stability**

Store in unopened original packaging and use within 12 months from the date of production .

#### **Free samples or learn more:**

Please contact: 006598831607 (Singapore) Mr. Yang